



New Cross-linkers for PDMS Networks

Bahrt, Frederikke; Daugaard, Anders Egede; Hvilsted, Søren; Skov, Anne Ladegaard

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Bahrt, F., Daugaard, A. E., Hvilsted, S., & Skov, A. L. (2011). *New Cross-linkers for PDMS Networks*. Abstract from 7th Annual Polymer Day, Kgs. Lyngby, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

New Cross-linkers for PDMS Networks

Frederikke Bahrt (frbah@kt.dtu.dk)¹, Anders E. Daugaard¹, Søren Hvilsted¹ and Anne Ladegaard Skov¹

¹Danish Polymer Center, Department of Chemical and Biochemical Engineering, Technical University of Denmark, Building 227, 2800 Kgs. Lyngby, Denmark



Dielectric electro active polymers (DEAPs) are polymeric network systems that can be used to convert an electrical input to mechanical deformation of a polymer. DEAPs can be applied as actuators, sensors and generators due to their ability to exhibit a change in size and shape when an external voltage is applied as well as generate electrical energy when the material is exposed to mechanically induced deformations. DEAPs are normally constructed from thin filled elastomer films with compliant electrodes on each side. Polydimethylsiloxane (PDMS) is one of the most used materials due to its natural high capacitance and good thermal stability, high efficiency and fast response.

The aim of this work is to design new PDMS networks applicable as DEAPs. One of the most important factors for DEAPs is the capacitance and development of novel materials are focused on increasing this while maintaining good mechanical properties. As PDMS has been used for DEAP applications with good results, it is of interest to do material optimization at the PDMS network cross-linking points as this could lead to material optimization. Design of novel functional cross-linkers can for example allow for incorporation of selected moieties in the network structure which could increase the dielectric permittivity and thereby the capacitance. Functional cross-linkers could also be used for investigation of the network formation and structure through labeling of cross-linking sites.

Potential functional cross-linkers should have selective functional groups to allow for specific cross-linking with PDMS chains at some reactive sites and chemical modification at other reactive sites. An example of a possible cross-linker is the readily available glucose, methyl- α -D-glucopyranoside, which contains four hydroxyl groups; three secondary and one primary. The secondary hydroxyl groups can be used as cross-linking sites for the PDMS chains, thus creating a network structure and the primary hydroxyl group can after chemical modification be used for selective reactions which will allow for specific reaction points in the PDMS network.

